

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : **05-255688**

(43)Date of publication of application : **05.10.1993**

---

(51)Int.Cl.

**C11B 9/00**

**A61K 7/00**

**A61K 7/46**

**C11B 9/02**

---

(21)Application number : **04-089811**

(71)Applicant : **KANEBO LTD**

(22)Date of filing : **13.03.1992**

(72)Inventor : **SAWADA KAZUHIKO**

---

### **(54) PERFUMERY AND COSMETIC CONTAINING SEDATIVE ESSENTIAL OIL**

#### **(57)Abstract:**

**PURPOSE:** To obtain a perfumery cosmetic containing an essential oil for sedation having excellent sedative effect and durability of the effect.

**CONSTITUTION:** The objective perfumery cosmetic contains a sedative essential oil obtained by removing high-boiling components from cedarwood oil and having a retention time of 0-50min [column; J&W Inc. DB-WAX (0.25mm inner diameter ×60m long); carrier gas, helium; flow rate of the carrier gas, 1mL/min; column temperature, 70-200°C; heating rate of the column, 2°C/min; detector, hydrogen flame ionization detector (F.I.D.)].

---

#### **LEGAL STATUS**

[Date of request for examination] **22.09.1997**

[Date of sending the examiner's decision of rejection] **28.09.1999**

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

**\* NOTICES \***

**JPO and NCIPi are not responsible for any damages caused by the use of this translation.**

1. This document has been translated by computer. So the translation may not reflect the original precisely.
2. \*\*\*\* shows the word which can not be translated.
3. In the drawings, any words are not translated.

---

**CLAIMS**

---

[Claim(s)]

[Claim 1] Perfumery and cosmetics characterized by containing the essential oil for killing which has the following property excluding the high-boiling point component from cedarwood oil.

In the chromatogram of the gas chromatography of the account following, a retention time should be less than 50 minutes from 0 minute.

Model: Hewlett Packard 5890A column: JIE and double company DB-WAX (bore [ of 0.25mm ] x die length of 60m)

carrier gas: -- helium carrier gas flow rate: -- a part for 1ml/-- column temperature: -- 70 - 200


Centigrade column programming-rate: -- a part for two Centigrade/-- detector: -- a hydrogen ion-ized detector (F. I.D.)

---

[Translation done.]

Drawing selection drawing 1 ☒

---



---

[Translation done.]